

NCK-3-26.5-1

3.5mm Connectors, DC~26.5GHz, Precision type



Features:
* High Precision

Applications:
* Calibration
* Laboratory Test

Description

With the components in these kits you can make error-corrected measurements of devices supplied with 3.5mm connectors from DC to 26.5 GHz.

Components

Part Number	Description	Frequency (GHz)	Impedance (Ω)	VSWR (Max.)	Phase Accuracy (°, Max.)	Inner Conductor	Outer Conductor	Size (mm)			
NO3C-M-26.5-1	3.5mm male open	DC~26.5	50	-	±1.5	Gold plated beryllium copper	Gold plated beryllium copper	-			
NO3C-F-26.5-1	3.5mm female open										
NS3C-M-26.5-1	3.5mm male short			-	±1.5			-			
NS3C-F-26.5-1	3.5mm female short										
NCT-3-C-M-26.5-1	3.5mm male termination			1.055	-			-			
NCT-3-C-F-26.5-1	3.5mm female termination										
NW-31-CK	3.5mm torque wrench			-	-			-	Tool steel (Head)	Aluminium oxide (Handle)	8.1 (Opening size)
NA33C-MM-1*	3.5mm male to 3.5mm male			1.06	-			-	Gold plated beryllium copper	Gold plated beryllium copper	-
NA33C-MF-1*	3.5mm male to 3.5mm female										
NA33C-FF-3*	3.5mm female to 3.5mm female										
Storage Box		-	-	-	-	Wood		275*200*80/ 145*145*60			

* ** Equal phase adapter

How To Order

NCK-3-26.5-1-10 All the 10 components in one box.

NCK-3-26.5-1-3M Three in one box, including open, short and termination, male, NO3C-M-26.5-1, NS3C-M-26.5-1, NCT-3-C-M-26.5-1.

NCK-3-26.5-1-3F Three in one box, including open, short and termination, female, NO3C-F-26.5-1, NS3C-F-26.5-1, NCT-3-C-F-26.5-1.

NCK-3-26.5-1-6 Six in one box, including NCK-3-26.5-1-3M and NCK-3-26.5-1-3F.

To order a single component, specify the part number in the first column.