

NCK-3-26.5-3

3.5mm Connectors, DC~26.5GHz, 3-in-1

Features:
* High Precision

Applications:
* Calibration
* Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with 3.5mm connectors from DC to 26.5 GHz.

Components

| Part Number | Description | Frequency | Impedance | VSWR | Phase Accuracy | Inner Conductor | Outer Conductor | Size |
|----------------------------|-----------------------------------|-----------|-----------|--------|----------------|------------------------------|------------------------------|------|
| | | (GHz) | (Ω) | (Max.) | (°, Max.) | | | (mm) |
| Opens | 3.5mm open | DC~26.5 | 50 | - | ±1.5 | Gold plated beryllium copper | Passivated stainless steel | - |
| Shorts | 3.5mm short | | | - | ±1.5 | | | - |
| Coaxial Terminations | 3.5mm termination | | | 1.055 | - | | | - |
| Connect Joint ¹ | | | | - | - | Aluminium oxide | | - |
| NA33C-MM-1 ² | 3.5mm male 3.5mm male adapter | | | 1.06 | - | Gold plated beryllium copper | Gold plated beryllium copper | - |
| NA33C-FF-3 ² | 3.5mm female 3.5mm female adapter | | | | | | | - |
| Storage Box | | | | - | - | - | - | Wood |

[1] The Connect Joint connects the Opens, Shorts and Coaxial Terminations

[2] Equal phase adapter

How To Order

NCK-3-26.5-3-M 3-in-1, male, including open, short and termination

NCK-3-26.5-3-F 3-in-1, female, including open, short and termination.

To order a single component, specify the part number in the first column.