

NCK-K-40-1

2.92mm Connectors, DC~40GHz, Precision type

Features:
* High Precision

Applications:
* Calibration
* Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with 2.92mm connectors from DC to 40 GHz.

Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size		
		(GHz)	(Ω)	(Max.)	(° , Max.)			(mm)		
NOKC-M-40-1	2.92mm male open	DC-40	50	-	±6	Gold plated beryllium copper	Gold plated beryllium copper	-		
NOKC-F-40-1	2.92mm female open			-	±4.5			-		
NSKC-M-40-1	2.92mm male short			-	-			-		
NSKC-F-40-1	2.92mm female short			-	-			-		
NCT-K-C-M-40-1	2.92mm male termination			1.08	-			-		
NCT-K-C-F-40-1	2.92mm female termination			-	-			-		
NW-K1-CK	2.92mm torque wrench			-	-			Nickel plated tool steel (Head)	Aluminium, anodised (Handle)	8.1 (Opening size)
NAKCC-MM*	2.92mm male to 2.92mm male adapter			1.15	-			Gold plated beryllium copper	Gold plated beryllium copper	-
NAKCC-MF*	2.92mm male to 2.92mm female									
NAKCC-FF*	2.92mm female to 2.92mm female									
Storage Box		-	-	-	-	Wood	275*200*80/ 145*145*60			

"" Equal phase adapter

How To Order



TOMORROW DISCOVERED

Calibration Kits

- NCK-K-40-1-10** All the 10 components in one box.
- NCK-K-40-1-3M** Three in one box, including open, short and termination, male, NOKC-M-40-1, NSKC-M-40-1, NCT-K-C-M-40-1.
- NCK-K-40-1-3F** Three in one box, including open, short and termination, female, NOKC-F-40-1, NSKC-F-40-1, NSKC-F-40-1.
- NCK-K-40-1-6** Six in one box, including NCK-K-40-1-3M and NCK-K-40-1-3F.

To order a single component, specify the part number in the first column.