

NCK-L1-9

L16 Connectors, DC~9GHz

Features:
* High Precision

Applications:
* Calibration
* Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with L16 connectors from DC to 9 GHz.

Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size		
		(GHz)	(Ω)	(Max.)	(°, Max.)			(mm)		
NOL1C-M-9	L16 male open	DC~9	50	-	±0.8	Gold plated beryllium copper	Passivated stainless steel	-		
NOL1C-F-9	L16 female open				-			-		
NSL1C-M-9	L16 male short			-	±0.8			-	-	
NSL1C-F-9	L16 female short			-	-			-	-	
NCT-L1-C-M-9	L16 male termination			1.032	-			-	-	
NCT-L1-C-F-9	L16 female termination			-	-			-	-	
NW-L11-CK	L16 torque wrench			-	-			Nickel plated tool steel (Head)	Aluminium, anodised (Handle)	19.1 (Opening size)
NAL1L1C-MM*	L16 male to L16 male adapter			1.06	-			Gold plated beryllium copper	Passivated stainless steel	-
NAL1L1C-MF*	L16 male to L16 female adapter									-
NAL1L1C-FF*	L16 female to L16 female adapter									-
Storage Box		-	-	-	-	Wood	275*200*80/ 145*145*60			

“*” Equal phase adapter

How To Order

NCK-L1-9-10 All the 10 components in one box.



TOMORROW DISCOVERED

Calibration Kits

- NCK-L1-9-1-3M** Three in one box, including open, short and termination, male, NOL1C-M-9, NSL1C-M-9, NCT-L1-C-M-9.
- NCK-L1-9-1-3F** Three in one box, including open, short and termination, female, NOL1C-F-9, NSL1C-F-9, NCT-L1-C-F-9.
- NCK-L1-9-1-6** Six in one box, including NCK-N-9-1-3M and NCK-N-9-1-3F.

To order a single component, specify the part number in the first column.