

NCK-N-6-1

N Connectors, DC~6GHz, Precision type

Features:

- * High Power
- * High Isolation
- * Low Insertion Loss
- * Low VSWR

Applications:

- * Wireless
- * Radar
- * Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with N connectors from DC to 6 GHz.

Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size	
		(GHz)	(Ω)	(Max.)	(° Max.)			(mm)	
NONC-M-6-1	N male open	DC~6	50	-	±0.6	Gold plated beryllium copper	Passivated stainless steel	-	
NONC-F-6-1	N female open			-	±0.6			-	
NSNC-M-6-1	N male short			-	±0.6			-	
NSNC-F-6-1	N female short			-	±0.6			-	
NCT-N-C-M-6-1	N male termination			-	1.025	-	Nickel plated tool steel (Head)	Aluminium, anodised (Handle)	-
NCT-N-C-F-6-1	N female termination			-	1.025	-			19.1 (Opening size)
NW-N1-CK	N torque wrench			-	-	-	-	-	-
NANNC-MM*	N male to N male adapter			1.05	-	-	Gold plated beryllium copper	Passivated stainless steel	-
NANNC-MF*	N male to N female adapter								-
NANNC-FF*	N female to N female adapter								-
Storage Box		-	-	-	-	Wood	275*200*80/ 145*145*60		

* * Equal phase adapter

How To Order

NCK-N-6-1-10 All the 10 components in one box.

NCK-N-6-1-3M Three in one box, including open, short and termination, male, NONC-M-6-1, NSNC-M-6-1, NCT-N-C-M-6-1.



TOMORROW DISCOVERED

NCK-N-6-1-3F Three in one box, including open, short and termination, female, NONC-F-6-1, NSNC-F-6-1, NCT-N-C-F-6-1.

NCK-N-6-1-6 Six in one box, including NCK-N-6-1-3M and NCK-N-6-1-3F.

Calibration Kits

To order a single component, specify the part number in the first column.