

NCK-N-9-1

N Connectors, DC~9GHz, Precision type

Features:

- * High Power
- * High Isolation
- * Low Insertion Loss
- * Low VSWR

Applications:

- * Wireless
- * Radar
- * Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with N connectors from DC to 9 GHz.

Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size		
		(GHz)	(Ω)	(Max.)	(°, Max.)			(mm)		
NONC-M-9-1	N male open	DC~9	50	-	±0.8	Gold plated beryllium copper	Passivated stainless steel	-		
NONC-F-9-1	N female open			-	-			-		
NSNC-M-9-1	N male short			-	±0.8			-		
NSNC-F-9-1	N female short			-	-			-		
NCT-N-C-M-9-1	N male termination			-	-	1.032	-	-	-	
NCT-N-C-F-9-1	N female termination			-	-	-	-	-	-	
NW-N1-CK	N torque wrench			-	-	-	-	Nickel plated tool steel (Head)	Aluminium, anodised (Handle)	19.1 (Opening size)
NANNC-MM*	N male to N male adapter			-	-	-	-	Gold plated beryllium copper	Passivated stainless steel	-
NANNC-MF*	N male to N female adapter			1.06	-	-	-			
NANNC-FF*	N female to N female adapter			-	-	-	-			
Storage Box		-	-	-	-	Wood		275*200*80/ 145*145*60		

“*” Equal phase adapter

How To Order

- NCK-N-9-1-10** All the 10 components in one box.
- NCK-N-9-1-3M** Three in one box, including open, short and termination, male, NONC-M-9-1, NSNC-M-9-1, NCT-N-C-M-9-1.
- NCK-N-9-1-3F** Three in one box, including open, short and termination, female, NONC-F-9-1, NSNC-F-9-1, NCT-N-C-F-9-1.
- NCK-N-9-1-6** Six in one box, including NCK-N-9-1-3M and NCK-N-9-1-3F.

To order a single component, specify the part number in the first column.