

NE086 Low PIM

Features:
* Low PIM

Applications:
* Phased-array Radar
* Instrument
* Interconnection in and between equipment

Electrical

Frequency: DC~40GHz
Cut-off Frequency: 64GHz
Impedance: 50Ω
Velocity of Propagation: 70%
Shielding Effectiveness: 165dB min.
Voltage Withstand: 400V DC


Mechanical

Bend Radius (installation): 7mm
Weight: 19g/m

Environmental

Temperature: -55~+125°C

Construction



No.	Name	Size (mm)	Material
1	Inner Conductor	0.53	Silver-plated copper
2	Dielectric	1.68	PTFE
3	Outer Conductor	2.18	Ternary alloy plated seamless copper tube

Attenuation & Power Handling

Frequency (GHz)	0.3	0.5	1	3	6	10	12.4	18	26.5	40
Attenuation*1 (dB/100m)	35.0	45.5	64.9	115.2	166.6	219.9	247.6	304.9	379.9	482.7
Average Power*2 (W)	475	366	256	144	100	76	67	55	44	34

[1] VSWR:1.0; Ambient: +25°C (77°F)

[2] VSWR:1.0; Ambient: +40°C (104°F); Sea level

Calculate Cable Attenuation: Attenuation (dB/100m) = $1.985320 * \sqrt{F} \text{ (MHz)} + 0.002140 * F \text{ (MHz)}$

Calculate Connector Attenuation: Attenuation (dB) = $0.03 * \sqrt{F} \text{ (GHz)}$

How To Order

NE086-X-Y-Z

X: Frequency in GHz

Y: Connector type

Z: Length in meters

Examples:

To order a NE086 cable assembly, DC-18GHz, SMA male to SMA female, 0.5 meter, specify NE086-18-SSF-0.5.

Connector naming rules:

2 - 2.4mm (40GHz, VSWR 1.35)

K - 2.92mm (40GHz, VSWR 1.35)

P - SMP (26.5GHz, VSWR 1.3)

A - SSMA (26.5GHz, VSWR 1.3)

S - SMA (26.5GHz, VSWR 1.3)

G - Mini-SMP (mateable with GPPO & SSMP, 18GHz, VSWR 1.3)

N - N (12GHz, VSWR 1.2)

X - MMCX (6GHz, VSWR 1.3)

M - MCX (6GHz, VSWR 1.3)

B - BNC (4GHz, VSWR 1.4)

D - SMB (4GHz, VSWR 1.25)

Female Connector - Add 'F' after connector name

Right Angle - Add 'R' after connector name (VSWR increase 0.1)

Mating Connector

NCG-FB-086-1

SSMP female, Beryllium copper



NCG-FRB-086-2

SSMP female, Right angle, Beryllium copper



NCK-MG-086-3

2.92mm male, Stainless steel



NCK-FB-086-1

2.92mm female, Brass



NCK-FL2G-A220-1

2.92mm female, 2-hole flange mount, Stainless steel

NCK-FL4G-A220-1

2.92mm female, 4-hole flange mount, Stainless steel

NCP-FB-086-3

SMP female, Beryllium copper

NCP-FRB-086-1

SMP female right angle, Beryllium copper



NCP-FRB-086-2

SMP female right angle, Beryllium copper



NCA-MG-086-2

SSMA male, Stainless steel

NCA-FHB-086-1

SSMA female bulk head, Brass

NCS-FL2B-086-1

SMA female, 2-hole flange mount, Brass

NCS-FL4B-086-1

SMA female, 4-hole flange mount, Gold plated beryllium copper

NCS-FHB-086-2

SMA female bulk head, Gold plated brass



NCN-MB-086-1

N male, Nickel plated brass



NCN-FB-086-1

N female, Nickel plated brass



NCX-MB-086-1

MMCX male, Gold plated brass



NCX-MRB-086-1

MMCX male right angle, Gold plated brass



NCX-FB-086-1

MMCX female, Gold plated brass

NCM-MB-086-1

MCX male, Gold plated brass



NCM-MRB-086-2

MCX male right angle, Gold plated brass/beryllium copper



NCM-FB-086-1

MCX female, Gold plated brass

Semirigid RF Cables & Assemblies

NCS-MB-086-4

SMA male, Gold plated brass



NCS-MG-086-3

SMA male, Stainless steel



NCS-MRG-086-1

SMA male right angle, Stainless steel



NCS-MRB-086-1

SMA male right angle, Gold plated brass



NCS-FB-086-2

SMA female, Gold plated brass



NCB-MB-086-1

BNC male, Ternary alloy plated brass



NCD-MB-086-1

SMB male, Gold plated brass

NCD-MRB-086-1

SMB male right angle, Gold plated brass

NCD-FB-086-1

SMB female, Gold plated brass

NCD-FRB-086-1

SMB female right angle, Gold plated brass