

NA23 2.4mm to 3.5mm

Features:
* Low VSWR

Applications:
* Wireless
* Transmitter
* Laboratory Test
* Radar

Electrical

Frequency:	DC~33GHz
VSWR:	1.15 max. 1.25 max. (right angle)
Impedance:	50Ω

Mechanical

RF Connectors:	2.4mm 3.5mm
Mating Life Cycle:	500 cycles
Outer Conductor:	Passivated Stainless Steel
Dielectric:	PEI
Inner Conductor:	Gold Plated Beryllium Copper

Environmental


Temperature: -60~+165°C

How To Order


- NA23-MM** - 2.4mm (m) to 3.5mm (m), Outline A
- NA23-MF** - 2.4mm (m) to 3.5mm (f), Outline B
- NA23-FM** - 2.4mm (f) to 3.5mm (m), Outline C
- NA23-FF** - 2.4mm (f) to 3.5mm (f), Outline D
- NA23R-MM** - 2.4mm (m) to 3.5mm (m), right angle, Outline E
- NA23R-MF** - 2.4mm (m) to 3.5mm (f), right angle, Outline F
- NA23R-FM** - 2.4mm (f) to 3.5mm (m), right angle, Outline G
- NA23R-FF** - 2.4mm (f) to 3.5mm (f), right angle, Outline H

Customization is available upon request.


Outline Drawings




Outline A




Outline B




Outline C




Outline D




Outline E



Outline F



Outline G



Outline H

Unit: mm [in]
Tolerance: ±0.2mm [±0.008in]