

NAKK

2.92mm to 2.92mm

Features:
* Low VSWR

Applications:
* Wireless
* Transmitter
* Laboratory Test
* Radar



Electrical

Frequency: DC~40GHz
VSWR: 1.15 max.
1.25 max. for right angle
Impedance: 50Ω

Mechanical

RF Connectors: 2.92mm
Mating Life Cycle: 2000 cycles
Outer Conductor: Passivated SUS303 Stainless Steel
Dielectric: PEI
Inner Conductor: Gold Plated Beryllium Copper

Environmental


Temperature: -60~+165°C

How To Order


- NAKK-FF** - 2.92mm (f) to 2.92mm (f), Outline A
- NAKK-MM** - 2.92mm (m) to 2.92mm (m), Outline B
- NAKK-MF** - 2.92mm (m) to 2.92mm (f), Outline C
- NAKKR-FF** - 2.92mm (f) to 2.92mm (f) right angle, Outline D
- NAKKR-MM** - 2.92mm (m) to 2.92mm (m) right angle, Outline E
- NAKKR-MF** - 2.92mm (m) to 2.92mm (f) right angle, Outline F
- NAKKH-FF** - 2.92mm (f) to 2.92mm (f) bulk head, Outline G
- NAKKH-MF** - 2.92mm (m) to 2.92mm (f) bulk head, Outline H
- NAKKL-FF** - 2.92mm (f) to 2.92mm (f) flange mount, Outline I

Customization is available upon request.


Outline Drawings




Outline A




Outline B




Outline C




Outline D




Outline E




Outline F



Outline G



Outline H



Outline I



Unit: mm [in]

Tolerance: ±0.2mm [±0.008in]